


V64A,B,C

- Compact size ,
withstanding 50kV;
- Long life with flexible
length of high voltage
leads;
- Easily mounting in any
axis and to the panel.



※ : Order the relay with the coil voltage in the part number as shown above. The coil voltage will appear on the coil plate near the coil terminals rather than in the pin on the relay.
※ ※ : Consult factory for load switching applications.

PRODUCT SPECIFICATIONS

Item	V64A	V64B	V64C
Contact Form	A	B	C
Contact Arrangement	SPST-NO	SPST-NC	SPDT
Contact Material (moveable/stationary)	molybdenum /tungsten		
Dielectric	Inert Gas		
Maximum Peak Test Voltage, Contacts and to Base (15µA Leak Current Max.) dc or 60Hz kV	55		
Maximum Peak Operating Voltage, Contacts and to Base (15µA Leak Current Max.) kV	dc or 60Hz	50	
	2.5MHz		
	13.56MHz		
	32MHz		
Current,Load Switching ※ ※	Contact factory		
Current, Continuous Carry Max A	dc or 60Hz	10	
	2.5MHz		
	13.56MHz		
	32MHz		
Coil Hi-Pot (V RMS, 60 Hz)	V	500	
Capacitance pF	Across Open Contacts		
	Contacts to Ground		
Operate Time	ms	15	
Release Time	ms	15	
Resistance, Contact Max @ 1A, 28 Vdc	Ω	1.0	
Operating Temperature Ambient	°C	-55 ~ +85	
Vibration, Operating, Sine (10-2000 Hz Peak) G's		10	
Shock, Operating, 1/2 Sine11ms (Peak) G's		10	
Life, Mechanical	Cycles	1 million	
Weight, Nominal	g(oz)	336(12)	

COIL RATINGS

Nominal, Volts dc	12	26.5	115
Pick-up, Volts dc, Max.	9	18	90
Drop-Out, Volts dc	.5~5	1~10	5~55
Coil Resistance (Ω ±10%)	18	75	1300

Ratings Listed are for 25°C, Sea Level Conditions

PART NUMBER SYSTEM

Series: High Voltage/Power **V64 C - 7 4 - 1**

Terminal Connections

A=SPST-NO, B=SPST-NC, C=SPDT

Coil Voltage ※: 7=12Vdc, 8=26.5Vdc, 9=115Vdc

High Voltage Connections: 4= Flying Leads, 12"

7= Flying Leads, 72" ; 8= Flying Leads, 36"

Mounting:

1= Threaded